SALAMATAK

PRODUCT DATA SHEET

TECTRA 11mm low stretch rope, white

RS110

Low stretch nylon rope for rope access, rescue and general work at height

Features:

- High specification
- Excellent handling
- Durable
- Compatible with heightec rope devices

3.2% shrinkage.

3.8% elongation in use

High twist yarn gives excellent handling & knotability.



Kernmantel rope has a core of parallel or braided strands (the core or kern) surrounded by a tightly woven sheath (mantel). The tightly woven sheath protects the core from UV light, cutting, dirt and abrasion.

Tectra ropes are specially designed for use in a wide range of situations and with modern rope devices. Low stretch ropes are suitable for suspension of a load yet capable of absorbing energy in the case of a fall with a fall factor less than one.

Minimum Breaking Loads (MBL):
32kN - unknotted
22kN - sewn
18kN - knotted

Options:
Black - RS110B
Gold - RS110G
Red - RS110R
Blue - RS110BL

Sold in 50m increments.

Weight: dependent on rope length e.g. 200m = 17kg

Specifications:

NB: specifications and colour may change without notice

Size:	50m, 100m, 150m, 200m lengths available
EN Test Mass:	
Loading:	32kN MBL (un-knotted), 22kN MBL (sewn), 18kN MBL (knotted)
Conformity:	EN1891 (A)
Materials:	Polyamide
Weight (kg):	85g/m
Industries:	All forms of work at height and rescue

SALAMATAK
للسلامة المهنية و الأمن الصناعي

All our PPE, rescue and lifting equipment have both UKCA and CE conformity where applicab